

Таблица1

Тип двигателя	Число полюсов	Габаритные размеры (мм)									
		l30	l33	h31	d24	l1	l2	l10	l31	d1	d2
AIP50	2; 4	178	200	130	120	20	20	63	32	9	9
AIP56	2; 4	203	230	141	140	23	23	71	36	11	11
AIP63	2; 4; 6	227	261	154	160	30	30	80	40	14	14
AIP71	2; 4; 6; 8	272,5	316,5	188	200	40	40	90	45	19	19
AIP80A	2; 4; 6; 8	296,5	350	204,5	200	50	50	100	50	22	22
AIP80B	2; 4; 6; 8	320,5	374	204,5	200	50	50	100	50	22	22
AIP90L	2; 4; 6; 8	337	390	205	250	50	50	125	56	24	24
AIP100S	2; 4	360	424	247	250	60	60	112	63	28	28
AIP100L	2; 4; 6; 8	391	455	247	250	60	60	140	63	28	28
AIP112M	2; 4; 6; 8	435	520	285	300	80	80	140	70	32	32
AIP132S	4; 6; 8	460	548	325	350	80	80	140	89	38	38
AIP132M	2; 4; 6; 8	498	584	325	350	110	110	178	89	38	38
AIP160S	2	630	750	385	350	110	110	178	108	42	42
	4; 6; 8	630	750	385	350	110	110	178	108	48	42
AIP160M	2	660	780	385	350	110	110	210	108	42	42
	4; 6; 8	660	780	385	350	110	110	210	108	48	42
AIP180S	2	630	744	440	400	110	110	203	121	48	48
	4	630	744	440	400	110	110	203	121	55	48
AIP180M	2	680	794	440	400	110	110	241	121	48	48
	4; 6; 8	680	794	440	400	110	110	241	121	55	48
AIP200M	2	735	846	485	450	110	110	267	133	55	55
	4; 6; 8	765	876	485	450	140	110	267	133	80	55
AIP200L	2	785	892	485	450	110	110	305	133	55	55
	4; 6; 8	815	922	485	450	140	110	305	133	60	55
AIP225M	2	835	952	535	550	110	140	311	149	55	60
	4	865	1012	535	550	140	140	311	149	65	60
	6; 8	820	967	535	550	110	140	311	149	65	60
AIP250S	2	880	1022	590	550	140	140	311	168	65	65
	4; 6; 8	880	1022	590	550	140	140	311	168	75	70
AIP250M	2	905	1047	590	550	140	140	349	168	65	65
	4; 6; 8	905	1047	590	550	140	140	349	168	75	70
AIP280M	2	1080	1360	660	660	140	140	419	190	70	70
	4	1180	1350	660	660	170	170	419	190	80	80
	6,8	1110	1350	660	660	170	170	419	190	80	80
AIP280S	2	1080	1320	660	660	140	140	368	190	70	70
	4,6,8	1110	1350	660	660	170	170	368	190	80	80
AIP315M	2	1260	1530	765	660	140	140	457	216	75	75
	4	1290	1530	765	660	170	170	457	216	90	90
	6,8,10	1290	1530	765	660	170	170	457	216	90	90
AIP315S	2	1160	1460	765	660	140	140	406	216	75	75
	4	1290	1460	765	660	170	170	406	216	90	90
	6,8,10	1190	1460	765	660	170	170	406	216	90	90
AIP355M	4,6,8	1450	1625	855	800	210	210	560	254	100	100
	10,12	1450	1625	855	800	210	210	560	254	100	100
AIP355S	4,6,8	1400	1595	855	800	210	210	500	254	100	100
	10,12	1400	1595	855	800	210	210	500	254	100	100

